



**Declaration of Performance (DoP) No. SPI004-2018**

1. **Unique identification code of product-type:**

Handmade Clay Roofing Tiles & Fittings

2. **Type, batch or serial number or any element allowing identification of the construction product as required pursuant to Article 11(4) of the CPR:**

Hanbury Handmade Nib Tiles (All Colours), Spicer Kent Peg Tiles (All Colours) & All Clay Fittings.

3. **Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Clay Roofing Tiles & Fittings for Pitched Roof Coverings and Wall Cladding (Vertical Tile Hanging).

4. **Name, registered trade name or registered trade mark and contact address of the manufacturer as required under article 11(5):**

A&A Spicer Holdings Ltd (T/A Spicer Tiles) , Swift Farm, Sandy Lane, Ashford, TN26 1JN

Company Reg No. 14301227

5. **Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12(2):**

Not Applicable

6. **System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:**

System 4

7. **In case of the declaration of performance concerning a construction product covered by a harmonized standard:**

BS EN 1304:2013

8. **In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

Not applicable





**9. Declared Performance Table 9.1 Roof Coverings**

Essential Characteristics	Performance	Harmonised Technical Specification
<b>Mechanical Resistance</b>	Complies	<b>BS EN 1304:2013</b>
<b>External Fire Performance</b>	Complies	
<b>Reaction To Fire</b>	Class A1	
<b>Water Impermeability</b>	Pass Category 1 - BS EN 539- 1:2005 Method 2	
<b>Dimensional Variation</b>	Complies	
<b>Durability Freeze-Thaw</b>	Pass - BS EN 539-2:2013 Test for Frost Resistance	
<b>Release of Dangerous Substances</b>	No Performance Determined	

**Table 9.2 External Wall Cladding and Internal Wall Lining**

Essential Characteristics	Performance	Harmonised Technical Specification
<b>Reaction To Fire</b>	A1	<b>BS EN 1304:2013</b>
<b>Water Impermeability</b>	Pass Category 1 - BS EN 539- 1:2005 Method 2	
<b>Durability Freeze-Thaw</b>	Pass - BS EN 539-2:2013 Test for Frost Resistance	
<b>Release of Dangerous Substances</b>	No Performance Determined	

**9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9**

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Mr A. Spicer**

**Director, A&A Spicer Holdings Ltd**

